


<b>ATTACCO RAPIDO</b> QUICK COUPLING	<b>CODICE</b> CODE	<b>ENTRATA</b> INLET	<b>FILETTATURA DI COLLEGAMENTO</b> COUPLING THREAD	<b>PRESSIONE</b> PRESSURE	<b>PORTATA</b> RATED FLOW/	<b>TEMPERATURA</b> TEMPERATURE
	(1) PW3001	G 3/8 F	G 1/ 2	250/280 bar – 3625/4060 psi	40 l/min	150 °C
	(2) PW3002	G 3/8 F	G 1/ 2	250/280 bar – 3625/4060 psi	40 l/min	150 °C
	(3) PW0212000140	G 3/8 M	G 1/ 2	250/280 bar – 3625/4060 psi	40 l/min	150 °C
	(4) PW300305	G 3/8 F	M22X1,5	250/280 bar – 3625/4060 psi	40 l/min	150 °C
	(5) PW0212003620	G 3/8 F	M22X1,5	250/280 bar – 3625/4060 psi	40 l/min	150 °C
	(6A) 28.0255.31	Ptgm. 17-19MM	Ø 22mm	10 bar – 145 psi	24 l/min	90 °C
	(6B) 28.0250.40	G 3/ 4 F	Ø 22mm	10 bar – 145 psi	24 l/min	90 °C
	(7A) 26.2035.61	G 3/8 F	Ø 19,9mm	220/250 BAR – 3200/3625 PSI	50 l/min	90 °C
	(7B) 26.2030.00	G 3/8 F	Ø 19,9mm	220/250 BAR – 3200/3625 PSI	50 l/min	90 °C